

Filter Products

IMAs

- Digital Frequency Discriminators
- Upconverters/Downconverters
- Amplified Preselectors
- Frequency Activity Detectors
- Frequency Multipliers

Switched Filter Banks

- High Isolation (>80 dB)
- Fast Switching Speeds (<25 ns)
- High Power (100 watts +)
- In-house Filter & Switch Design
- Multiple Control Interfaces (LVTTTL, RS-232, USB)


Filter Optimization

- Cavity
- Lumped Element
- Ceramic
- SAW
- Suspended Substrate

High Performance, Fully Customizable Multi-Channel Filter Assemblies

- Bandpass, Lowpass, Highpass, Bandreject
- Duplexers/Diplexers, Triplexers, Multiplexers
- Dielectrically Loaded Cavity Filters, Duplexers & Multiplexers
- Low Cost Ceramic
- Cavity / Combine, TEM
- Lumped Element
- Suspended Substrate
- SAW
- Waveguide

Integrated Microwave Assemblies



Switched Filter Banks



Filters

Complexity


Wireless Assemblies & Sub-Systems

- Multiplexers
- PIN Diode Switch Filters
- Filtered GPS LNAs
- Integrated Switch Filter Banks
- High Power Amplifier + Filter Assemblies

Co-Site Interference Mitigation Filters

Broad Filter Capability Supporting Optimization of Program Performance, Size and Cost Requirements

- Lumped Element Filters
- Cavity /Comblne/Interdigital Filters
- Tubular Filters
- Waveguide Filters
- Ceramic
- Suspended Substrate Stripline
- Surface Acoustic Wave (SAW)
- Diplexers & Multiplexers




Filter Manufacturing Capabilities

Prototype/ Production Centers

Prototype Machine



CMM (Coordinate Measurement Machine)



Laser Welding



Fabrication & Assembly

J-STD-001, Class 3 Soldering



SMT/Pick n Place



Miniature Assembly



Electrical & Environmental Testing

Automated Test & Data Recording



Extensive Burn-in and Thermal Cycling Capabilities



Shock & Vibration Testing



The Filter Specialists

Our customers are able to weigh the benefits of...

- Size vs. Loss
- Rejection vs. Size
- Selectivity vs. Group Delay

...and select the perfect filter to optimize system performance and value.

Bandpass Filters

Bandpass filters are available with nearly every topology including:

- SAW
- Cavity
- Lumped Element
- Tubular
- Suspended Substrate
- Ceramic
- Waveguide



Lowpass Filters

Lowpass are available with the following topologies:


- Lumped Element
- Tubular
- Suspended Substrate

Our expert engineers can utilize multiple topologies in a single design!

Highpass Filters

Highpass filters are available with the following topologies:

- Lumped Element
- Suspended Substrate



Band Reject/Notch


Notch filters are available with the following topologies:

- Cavity
- Lumped Element
- Suspended Substrate
- Ceramic
- Waveguide



Diplexers, Triplexers, Multiplexers

Suspended Substrate is the ideal topology for broadband contiguous multiplexers. We also provide multiplexers utilizing lumped component and cavity based structures.



Filter Topologies

Lumped Element

Features

- 300 kHz to 10 GHz
- Smallest and lightest
- Versatile topologies and transfer functions
- Ideal for moderate to very wide bandwidths
- Connectorized or surface mount
- Easily multiplexed
- Temperature stable options
- RoHS Compliance

Our custom package concepts provide additional shielding for better ultimate rejection.

We use creative layouts which offer reduced package sizes when needed.


Cavity

Features

- 400 MHz to 40 GHz
- Low insertion loss
- High selectivity Chebyshev and pole-placed
- Temperature stable options
- High power handling capability
- 0.1 to +60% bandwidth
- Low profile designs available
- Drop-in designs to 20 GHz
- Low intermodulation products

Our custom package concepts provide additional shielding for better ultimate rejection.

We use creative layouts which offer reduced package sizes when needed.




Ceramic

Features


- Frequency range - 400 MHz to 6 GHz
- Bandwidths - 1 to 10%
- 2 to 6+ sections, custom packages available
- Low cost, small size
- Good insertion loss relative to size
- Surface mount
- Open frame or sealed for hi-rel
- Typical applications are:
 - GPS
 - ISM
 - WLAN
 - IFF
 - ManPack

Gold plating on surface mount packages offers better solderability & corrosion resistance




Temperature Stabilizing Elastomers for:

- Harsh Temperature Environments
- Demanding Shock & Vibration Specifications



Capacitive coupling arrays offer:

- Design Flexibility
- Superior Performance
- Enhanced Reliability
- Enhanced Repeatability




Suspended Substrate



Features

- 2 to 40 GHz
- Ideal for broadband multiplexing
- Chebyshev and elliptic response
- Well suited for high shock and vibration applications
- Highly repeatable (ideal for matched filters)
- Broadband receivers
- Easily integrated with other components

We also offer immersion silver plating for very low loss designs



Suspended Substrate Quadraplexer



Surface Acoustic Wave (SAW)

Features

- Frequencies from 20 MHz to 2600 MHz
- Fractional Bandwidths 0.04 to 60%
- Hermetically Sealed

Available Options

- Available Options
- Low Loss Performance (< 2 dB)
- Shape Factors Below 1.10:1
- Customized Designs for Specific Applications

Tubular/Coaxial

Features

- 30 MHz to 5 GHz
- Broad Stopbands
- Ideal for Harmonic Rejection
- Moderate Bandwidths (2 to 50%)
- Chebyshev Transfer Functions
- High Power Handling Capability
- High Power Tubular Designs to 5000 watts
- Low Loss and High Ultimate Rejection
- Consistent Unit to Unit Performance
- Utilizing Precision Centerless Ground Stock
- Lowpass or Bandpass Configuration
- High Shock Rugged Mounting Configurations Available

Waveguide

Features

- 2 to 40 GHz
- Bandwidths 0.1 to 10%
- Extremely Low Insertion Loss
- High Power Handling
- RX/TX Waveguide Diplexers in Custom Configurations
- Waveguide Flanges are Standard
- SMA, TNC, or Type-N Connectors Available
- Integral Heat Sink

Rapid Filter Centers


Lumped Element rapid cell filters with the following options:

- Bandpass, Lowpass, Highpass or Band Reject (Notch)
- SMA Connectors, Surface Mount or PC Pin Options
- 1 MHz to 3 GHz

Rapid filter solutions are for moderate complexity, standard design options only.

Filters within these restraints (for selected applications) can be delivered in as little as 2-4 weeks.

Please contact the factory for details and to find out if your requirements fall within these guidelines.




Cavity rapid cell filters with the following options:

- Bandpass
- SMA Connectors
- 800 MHz to 20 GHz

Rapid filter solutions are for moderate complexity, standard design options only.

Filters within these restraints (for selected applications) can be delivered in as little as 2-4 weeks.

Please contact the factory for details and to find out if your requirements fall within these guidelines.



Ceramic rapid cell filters with the following options:

- Bandpass
- Surface Mount
- 400 MHz – 2,500 MHz

Rapid filter solutions are for moderate complexity, standard design options only.

Filters within these restraints (for selected applications) can be delivered in as little as 2-4 weeks.

Please contact the factory for details and to find out if your requirements fall within these guidelines.



Quality And Reliability

Superior Quality

Our employees:

- Are encouraged to suggest product improvements
- Have the skills and tools to identify the slightest imperfections
- Continually strive to exceed the goals placed before them
- Know that our success is directly related to the satisfaction of our customers

Rapid filter solutions are for moderate complexity, standard design options only.

Filters within these restraints (for selected applications) can be delivered in as little as 2-4 weeks.

Please contact the factory for details and to find out if your requirements fall within these guidelines.

**All Manufacturing Facilities Certified to
ISO 9001:2008
Six Certified AS9100 Facilities (more
facilities to be certified soon!)**

During the design & development process, our engineers incorporate preventative design best practices such as:

- Spring-loaded, self-locking tuning bushings and rotors reducing the risk of metallic slivers which can lead to premature failure in cavity designs.
- Annealing of all inductors to remove any metal stress memory for consistent and reliable inductor performance.
- Designs incorporating smooth angles and edges for superior plating adhesion and higher operating power.

Quality Planning

As part of our Quality Management System (QMS) planning we utilize state of the art quality tools including APQP (Advanced Product Quality Planning), Control Plans and FMEA (failure modes effects analysis) that result in robust product realization strategies with the result of proactively engineering out potential quality problems.

Process Monitoring

We monitor established control points of product realization with proprietary data logging technology which allows for regular and critical assessment of performance against QMS objectives and product capability expectations.


Engineering Capabilities

State-of-the-Art Engineering

Using state-of-the-art software and simulation tools, our experienced engineering team is able to quickly take a requirement from concept to production.

Tools and software our Engineers routinely use:

- Ansoft HFSS
- Microwave Office
- Agilent ADS Design Suite
- SolidWorks
- Labview
- Agilent Genesys
- AutoCAD
- Cadence Allegro
- Ansoft Designer
- Sonnet EM Simulator



3D modeling is used to ensure component compatibility and assess tolerance stack-ups.

Partnering with our Customer

Using Genesys and CAD models allows us to integrate the Filter into our customer's system level assembly to ensure proper fit and overall integrity.

RF, Microwave & Microelectronics

Spectrum Control is a top provider of precision-engineered, high-performance RF & microwave and microelectronic solutions for high-reliability and mission-critical applications in the global defense, commercial, and space markets.

- 13 locations worldwide dedicated to the design, development and manufacture of one of the **world's largest selections** of RF/microwave components and subsystems
- 70+ years of extensive and diverse **program experience**
- **Preferred Supplier** status at many major primes
- **Engineering** accounts for **14%** of the team's overall composition
- Dedication to quality; **AS9100** and **ISO 9001** certified

